LINK NAME	Descriptive name for the link contained on that tab.
Sample Task Order #:	Indicate the STO to which the Contractor is responding.
DATE	Date link budget prepared
1a. Satellite Name	Name of satellite being proposed
1b. Satellite Longitude (West/East) [deg]	Orbital location of satellite
1c. Uplink/Downlink Beam	Uplink/Downlink Beam name on which proposed transponder is located (ie. MEK, NA, Regional, etc.)
1d. Transponder Id	Name of transponder (ie. 23k, NEAVA4, etc.)
1e. Type of Band (C,Ku,C/Ku,Ku/C,X)	Band of beam provided
1f. Xpdr Total Bandwidth [MHz]	Total BW on proposed transponder
1g. UL Beam Polarization (V,H,L,R)	Uplink polarization
1h. DL Beam Polarization (V,H,L,R)	Downlink polarization
1i. Xpdr SFD (@ 0 dbi/K G/T) [dBW/m2]	Current or proposed SFD setting of transponder
2a. Data Rate (including "Overhead") [kbps]	Total Data rate of proposed carrier
2b. Modulation Scheme (1-BPSK,2-QPSK,3-8PSK ... others)	Modulation used for proposed carrer

7a. C/No Overall [dBHz]	Overall (uplink and downlink) ratio of carrier power over noise and all interferences.
7b. System Link Margin (including Rain Model) [dB]	Difference between Required Eb/No and target Eb/No including margins to overcome rain fade and interference
7c.Total Link Availability (end-to-end) [%]	Calculated availability based on ITU Rain Fade Models and interference

7d. Required Thresh. Eb/No + Sys. Link Margin [(l)-1.5 (c)-4 d 65.08 (d)-0.6 (e)5.2 DC q265.08 703.8 2116 (/MCID 23 DC q265.08 685.8 211.081 17.04 reW nBEW nBEW n20.6 (r)3.7 (e)5.2

Site A to Site B		STO # 1	29-Oct-15
Satellite & Carrier Characteristics			
1. Satellite Characteristics		**2. Carrier Parameters**	
1a. Satellite Name	E 70A	2a. Data Rate (including "Overhead") [kbps]	8192
1b. Satellite Longitude (West/East) [deg]	116 E	2b. Modulation Scheme (BPSK, QPSK, 8PSK … others)	QPSK
1c. Uplink/Downlink Beam	Fixed	2c. Coding Type (Conv., Conv+RS, TPC, LDPC)	Conv+RS
1d. Transponder Id	D1	2d. Inner Code Rate (FEC Rate/Code Rate)	0.875
1e. Type of Band (C,Ku,C/Ku,Ku/C,X)	Ku	2e. Outer Code Rate (e.g. Reed/Solomon)	(219/201)
1f. Xpdr Total Bandwidth [MHz]	72.00	2f. Rolloff Factor/Spacing Factor	1.35
1i. UL Beam Polarization (V,H,L,R)	Y	2g. Required Eb/No Threshold [dB]	6.9
1j. DL Beam Polarization (V,H,L,R)	X	2h. Bit Error Rate (BER)	1.0E-07
1k. Xpdr SFD (@ 0 dBi/K G/T) [dBW/m2]	-78.00		
Terminal Characteristics			
3. Transmitting Terminal Tx		**4. Receiving Terminal Rx**	
3a. Location Name	Site A	4a. Location Name	Site B
3b. Terminal Id (Name/Number)	OKET 13	4b. Terminal Id (Name/Number)	OKET 48
3c. Uplink Frequency [GHz]	13.79167	4c. Downlink Frequency [GHz]	11.49167
3d. Latitude (plus for North) [deg]	Numbers	4d. Latitude (plus for North) [deg]	Numbers
3e. Longitude (West/East) [deg]	Numbers	4e. Longitude (West/East) [deg]	Numbers
3f. Elevation Angle [deg]	53.63	4f. Elevation Angle [deg]	62.54
3g. Tx Dish Size [m]	4.80	4g. Rx Dish Size [m]	3.80
3h. Uplink Tx EIRP @ Tx [dBW]	62.34	4h. G/T of Rx [dB/K]	30.60
3i. Satellite Footprint G/T @ Tx [dB/K]	3.50	4i. Satellite Footprint EIRP @ Rx [dBW]	40.50
Link Budget with Included Rain Model			
5. Uplink		**6. Downlink**	
5.a. Carrier Output Backoff at Tx Earth Station [db]	18.58	6a. Carrier Output Backoff at Transmitting Transponder [dB]	13.88
5b. Up Link Free Space Loss [dB]	206.56	6b. Down Link Free Space Loss [dB]	204.87

5cTm[(p)-11.8 (R Tm[(5)8 (. U)11.8 (p)8.8 (lin)8.9 (k)]TETEMC /P.008 Tw 250.68 689.04 9.96 reW nBT/TT0 1 Tf0.006 Tc 8.88 -0 0 8.88 48.72 253.32 Tm[(5)8 (. U)11.8 (p

Site B to Site A		STO # 1	29-Oct-15
Satellite & Carrier Characteristics			
1. Satellite Characteristics		**2. Carrier Parameters**	
1a. Satellite Name	E 70A	2a. Data Rate (including "Overhead") [kbps]	8192
1b. Satellite Longitude (West/East) [deg]	116 E		

TDMA to worst case scenario		STO # 2	29-Oct-15
Satellite & Carrier Characteristics			
1. Satellite Characteristics		**2. Carrier Parameters**	
1a. Satellite Name	E 70A		